



DESIGNJET L25500 PRINTER SERIES



Increase business opportunities with a printer that delivers unrivaled versatility for outdoor and indoor applications.⁽¹⁾ Experience the ease of reliable HP Designjet printing. Attract the attention of environmentally conscious customers.



UNRIVALED VERSATILITY FROM ONE PRINTING SYSTEM⁽¹⁾

- Produce outdoor signage with durability comparable to eco-solvent inks.⁽²⁾
- Achieve high-quality results—that meet clients' branding requirements—for all your indoor signage applications, from exhibition graphics to interior decorations.
- Print on a wide range of media, including coated media or polyester fabric⁽³⁾ and low-cost papers without treatments.
- Produce vehicle wraps with HP Latex Inks that outperform eco-solvent inks. HP is the only company that offers and warrants the entire printing system for vehicle wraps⁽⁴⁾ with the HP Performance Warranty for HP Air Release Adhesive Gloss Cast Vinyl and HP Clear Gloss Cast Overlaminate.⁽⁵⁾
- Expect the most out of each application when you use the broad portfolio of Original HP printing materials.

EASY, AUTOMATIC, LOW MAINTENANCE PRINTING

- Experience easy, unattended printing with HP Thermal Inkjet printheads and automatic maintenance.
- Experience greater uptime—with user-replaceable printheads you can avoid the delay and expense of a service call.
- Automatically achieve high image quality and consistency with the HP Optical Media Advance Sensor (OMAS) and embedded spectrophotometer.
- Post-print production is easy with prints that come off the printer dry and ready—for lamination, packaging, shipping, and display.
- Minimize interruptions with pro-active alerts and the embedded Web server, which is accessible through your preferred RIP.

GO GREEN, IMPROVE YOUR OPERATOR'S WORK ENVIRONMENT

- Provide your print operators with an improved working environment—without the health and safety considerations of printshops that use eco-solvent-based printers.
- Build a competitive edge with odorless prints⁽⁶⁾ ideal for sensitive indoor areas. HP Latex Ink prints on HP PVC-free Wall Paper meet the GREENGUARD Children & Schools standard for low emitting products⁽⁷⁾ and AgBB criteria for health-related evaluation of VOC emissions of indoor building products.⁽⁸⁾
- No special ventilation equipment⁽⁹⁾ or external dryer requirement helps keep energy costs down.
- Distinguish your business and attract new environmentally focused customers by offering a complete solution—including water-based HP Latex Inks and HP recyclable media.⁽¹⁰⁾
- Take advantage of free, convenient HP programs for recycling Original HP 789 Ink Cartridges, Printheads, and cleaning supplies⁽¹¹⁾, as well as prints produced on HP recyclable media.⁽¹⁰⁾



ecOHIGHLIGHTS

HP DESIGNJET L25500
PRINTER SERIES

- Water-based HP Latex Inks—no hazard warning labels, no HAPs⁽¹⁾
- No special ventilation required⁽²⁾
- Odorless prints;⁽³⁾ printed HP wall paper meets GREENGUARD and AgBB criteria⁽⁴⁾
- Range of recyclable HP media available, with take-back program⁽⁵⁾
- ENERGY STAR[®] qualified product

⁽¹⁾ Contains no Hazardous Air Pollutants according to EPA Method 311.
⁽²⁾ Special ventilation is not required to meet US OSHA requirements on occupational exposure to VOCs from HP Latex Inks. Special ventilation equipment installation is at the discretion of the customer—no specific HP recommendation is intended. Customers should consult state and local requirements and regulations.
⁽³⁾ Some substrates may have an inherent odor.
⁽⁴⁾ HP PVC-free Wall Paper printed using HP Latex Inks meets GREENGUARD Children & Schools criteria for low emitting products and AgBB criteria for health-related evaluation of VOC emissions of indoor building products.
⁽⁵⁾ Program availability varies. Please check www.hp.com/recycle for details.

www.hp.com/ecosolutions

Please recycle your computing hardware and printing supplies.
Find out how at our website.





HP DESIGNJET L25500 PRINTER SERIES



SAVE TIME AND EXPENSE WITH USER-REPLACEABLE PRINTHEADS

The HP Designjet L25500 Printer series is designed to save you time and money. Printheads you can replace yourself eliminate the down-time and expense of a service call. And fully-automatic printhead testing and maintenance systems eliminate time-consuming daily manual maintenance.



GET HIGH PERFORMANCE

WITH HP DOUBLE SWATH TECHNOLOGY

The HP Designjet L25500 uses pairs of staggered printheads in HP Double Swath Technology for a wide (1.7 inch/43.2 mm) print swath and higher throughput. To eliminate swath-to-swath banding, the print swaths overlap each other and nozzles printing in the same scan line (top and bottom printheads) are used together.



ELIMINATE WAITING TIME WITH PRINTS THAT ARE COMPLETELY DRY RIGHT OFF THE PRINTER

Win business with faster turnaround times. Prints come out of the printer completely dry, so there's no waiting before you move on to lamination, finishing, or packing for shipment.



REVOLUTIONARY HP LATEX INK TECHNOLOGIES HAVE THE POWER TO CHANGE YOUR FUTURE.

Innovative **HP Latex Inks** produce prints with the quality and durability of eco-solvent and low-solvent ink technologies⁽²⁾ but they're water-based inks. So you get the application versatility, without the hassle associated with the environmental, health, and safety considerations of solvent-based inks.



PRODUCE

A REMARKABLY BROAD RANGE OF OUTDOOR AND INDOOR APPLICATIONS
From rugged, eye-catching vehicle wraps that get ad campaigns moving to odorless⁽⁶⁾ indoor displays perfectly suited for sensitive hospital or restaurant environments, HP Latex Ink Technologies provide you with the opportunity to print on a wide range of solvent-compatible media including most low-cost uncoated media. **Expand your offering** and watch your print volumes grow.

To learn more about innovative HP Latex Ink Technologies, see:
WWW.HP.COM/GO/HP_LATEX_PRINTING_TECHNOLOGIES



ACHIEVE QUALITY AND CONSISTENCY WITH THE OPTICAL MEDIA ADVANCE SENSOR AND OPTICAL DROP DETECTOR

Featuring sophisticated media advance controls and automatic nozzle testing, this printer is designed to produce defect-free prints that help you avoid ink and media waste. The HP Optical Media Advance Sensor (OMAS) controls the media as it advances through the printer to minimize banding at high speeds. The Optical Drop Detector (ODD) automatically tests the drop ejection performance of every printhead nozzle to produce prints free of defects.



PROACTIVELY MANAGE YOUR PRINT JOBS WITH THE EMBEDDED WEB SERVER

Accessible using your preferred web browser, the embedded Web server allows you to control print settings and monitor your printer's use of ink and media. Gain tighter control over your print jobs and prevent unnecessary ink and media waste.



PRINT CONTINUOUS, UNATTENDED RUNS WITH THE TAKE-UP REEL, INCLUDED STANDARD

Improve productivity by printing continuous, unattended runs—even overnight—and on long media rolls with the media take-up reel that comes standard on both 42-inch and 60-inch models of this printer.



LEAVE BEHIND THE HIGH MAINTENANCE AND SPECIAL REQUIREMENTS

No hazard warning labels and no special ventilation requirements⁹ can add up to **less hassle** and expense—and improve the work environment for your employees.



HELP YOUR BUSINESS, AND YOUR CUSTOMERS, GO GREEN

Offer your customers prints produced on **recyclable¹⁰ and PVC-free** Original HP printing materials, and reduce the impact of printing on the environment.



INDOOR QUALITY
+

OUTDOOR DURABILITY



LATEX INKS



Eco-solvent ● + ● Water-based

LATEX INKS PROVIDE THE DURABILITY AND COST ADVANTAGES of eco-solvent inks AND the environmental improvements of water-based inks.



HP DESIGNJET L25500 PRINTER SERIES

TECHNICAL SPECIFICATIONS

| | |
|---|---|
| Print speed¹² | |
| | Up to 22.8 m ² /hr (246 ft ² /hr) |
| Media | |
| Handling | Roll feed, take-up reel, automatic cutter for vinyl, paper-based media, backlit polyester film, and thin banners |
| Types | Banners, vinyls, films, fabrics, papers, mesh with liner |
| Size | 42-in models: 58 to 106.7-cm (23 to 42-in) rolls, up to 28 kg (61.7 lb) 60-in models: 58 to 152.4-cm (23 to 60-in) rolls, up to 40 kg (88 lb) |
| Loading | Rolls up to 18 cm (7.1 in) outside diameter |
| Thickness | Up to 0.5 mm (19.7 mil) |
| Printing modes¹² | |
| 4-pass bidirectional | 22.8 m ² /h (246 ft ² /hr) |
| 6-pass bidirectional | 16.5 m ² /h (178 ft ² /hr) |
| 8-pass bidirectional | 10.6 m ² /h (114 ft ² /hr) |
| 10-pass bidirectional | 9.0 m ² /h (97 ft ² /hr) |
| 12-pass bidirectional | 7.6 m ² /h (81 ft ² /hr) |
| 16-pass bidirectional | 6.3 m ² /h (68 ft ² /hr) |
| Printing | |
| Print resolution | 1200 x 1200 dpi |
| Margins (top x bottom x left x right) | 5 x 5 x 5 x 5 mm (0.2 x 0.2 x 0.2 x 0.2 in) |
| Technology | HP Thermal Inkjet |
| Ink types | HP Latex Inks |
| Ink colors | Cyan, magenta, yellow, black, light cyan, light magenta |
| Ink drop | 12 pl |
| Ink cartridge size | 775 ml |
| Printheads | 6 (2 x yellow/black, 2 x cyan/light cyan, 2 x light magenta/magenta) |
| Nozzles | 2112 per printhead (2 colors per printhead, 1056 nozzles per color) |
| Maximum print length | No physical limit (determined by RIP software or media roll length) ¹³ |
| Connectivity | |
| Interfaces (standard) | Gigabit Ethernet (1000Base-T) |
| Dimensions (w x d x h) | |
| Printer | 42-in models: 1985 x 690 x 1370 mm (78 x 27.5 x 54 in) 60-in models: 2465 x 690 x 1370 mm (97 x 27.5 x 54 in) |
| Shipping | 42-in models: 2230 x 810 x 1184 mm (87.8 x 31.9 x 46.6 in) 60-in models: 2690 x 810 x 1184 mm (105.9 x 31.9 x 46.6 in) |
| Weight | |
| Printer | 42-in models: 161 kg (355 lb) 60-in models: 181 kg (399 lb) |
| Shipping | 42-in models: 250 kg (550 lb) 60-in models: 310 kg (682 lb) |
| What's in the box | |
| | Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords |
| Environmental ranges | |
| Operating temperature | 15 to 30° C (59 to 86° F) |
| Recommended operating temperature | 18 to 25° C (64 to 77° F) |
| Storage temperature | -25 to 55° C (-13 to 131° F) |
| Recommended operating humidity | 20 to 80% RH (non-condensing) |
| Acoustic | |
| Sound pressure, active | 56 dB(A) |
| Sound pressure, standby | 39 dB(A) |
| Sound power, active | 7.5 B(A) |
| Sound power, standby | 5.1 B(A) |
| Power consumption | |
| Maximum | 42-in models: 3.5 kW maximum (only when warming up) 60-in models: 4.8 kW maximum (only when warming up) |
| Active | 42-in models: 1.8 kW 60-in models: 2.6 kW |
| Heat dissipation | 42-in models: 12.3 kBtu/hr 60-in models: 16.4 kBtu/hr |
| Powersave | < 72 watts |
| Off | 0.4 watts |
| Power requirements | 42-in models: Input voltage (auto ranging) 200 to 240 VAC (-10% +6%), 50/60 Hz (+/- 3 Hz), 13 A max per power cord 60-in models: Input voltage (auto ranging) 220 to 240 VAC (-10% +6%), 50/60 Hz (+/- 3 Hz), 15 A max per power cord |
| Certification | |
| Safety | USA and Canada (CSA certified), EU (LVD and EN 60950-1 compliant), Russia (GOST), China (CCC) |
| Electromagnetic | Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) |
| Environmental | WEEE, EU RoHS, China RoHS, REACH, EuP, FEMP |
| ENERGY STAR [®] qualified models | see: www.hp.com/go/energystar |
| Warranty | |
| | One-year limited hardware warranty; 8-hour, 5 days a week phone support |

ORDERING INFORMATION

| | |
|---|---|
| Product | |
| CH955A | HP Designjet L25500 42-in Printer |
| CH956A | HP Designjet L25500 60-in Printer |
| Accessories | |
| CQ692A | HP Designjet L25500 42-in Printer 2-in Spindle |
| CQ154A | HP Designjet L25500 42-in Printer 3-in Spindle |
| CQ693A | HP Designjet L25500 60-in Printer 2-in Spindle |
| CQ155A | HP Designjet L25500 60-in Printer 3-in Spindle |
| Original HP printheads | |
| CH612A | HP 789 Yellow/Black Designjet Printhead |
| CH613A | HP 789 Cyan/Light Cyan Designjet Printhead |
| CH614A | HP 789 Light Magenta/Magenta Designjet Printhead |
| Original HP ink cartridges | |
| CH615A | HP 789 775-ml Black Latex Designjet Ink Cartridge |
| CH616A | HP 789 775-ml Cyan Latex Designjet Ink Cartridge |
| CH617A | HP 789 775-ml Magenta Latex Designjet Ink Cartridge |
| CH618A | HP 789 775-ml Yellow Latex Designjet Ink Cartridge |
| CH619A | HP 789 775-ml Light Cyan Latex Designjet Ink Cartridge |
| CH620A | HP 789 775-ml Light Magenta Latex Designjet Ink Cartridge |
| Original HP maintenance supplies | |
| CH621A | HP 789 Designjet Printhead Cleaning Kit |
| CH622A | HP 789 Designjet Printhead Cleaning Container |
| Original HP printing materials | |
| Banners | |
| | HP HDPE Reinforced Banner—recyclable ¹⁰ |
| | HP Durable Frontlit Scrim Banner |
| | HP Outdoor Frontlit Scrim Banner |
| Self-adhesive materials | |
| | HP Air Release Adhesive Gloss Cast Vinyl |
| | HP One-view Perforated Adhesive Window Vinyl |
| | HP Permanent Gloss Adhesive Vinyl |
| | HP Permanent Matte Adhesive Vinyl |
| Polyester fabrics | |
| | HP Heavy Textile Banner—recyclable ¹⁰ |
| | HP Light Textile Display Banner—new, recyclable ¹⁰ |
| | HP Wrinkle-free Flag with Liner—recyclable ¹⁰ |
| Papers/photographic papers | |
| | HP PVC-free Wall Paper |
| | HP White Satin Poster Paper—recyclable ¹⁰ |
| | HP Photo-realistic Poster Paper—recyclable ¹⁰ |
| | HP Blue Back Billboard Paper |
| Specialty materials | |
| | HP DuPont™ Tyvek® Banner—recyclable ¹⁰ |
| | HP Safin Canvas |
| Service and support | |
| US218E | 3 year, Next business day, Onsite, Designjet L25500 60-inch Support |
| US211E | 3 year, 4 hour response 13 by 5 Onsite, Designjet L25500 60-inch Support |
| US212PE | 1 year, Post Warranty, Next business day, Onsite, Designjet L25500 60-inch Support |
| US206PE | 1 year, Post Warranty, 4 hour response 13 by 5 Onsite, Designjet L25500 60-inch Support |
| US203E | 3 year, Next business day, Onsite, Designjet L25500 42-inch Support |
| US196E | 3 year, 4 hour response 13 by 5 Onsite, Designjet L25500 42-inch Support |
| US197PE | 1 year, Post Warranty, Next business day, Onsite, Designjet L25500 42-inch Support |
| US191PE | 1 year, Post Warranty, 4 hour response 13 by 5 Onsite, Designjet L25500 42-inch Support |

For more HP large-format printing materials and sizes please visit us online at: www.hp.com/go/lfp/Printing/materials-supplies

Software: For HP Certified third-party RIP solutions, please visit us online at: www.hp.com/go/L25500/solutions

See Site Preparation Guide requirements to ensure complete compliance with all installation and operation requirements, safety procedures, warnings, cautions, and local regulations. Download this and other manuals from: www.hp.com/go/L25500/manuals

- The HP Designjet L25500 Printer produces an extremely broad range of both outdoor and indoor applications from a single device, which surpasses the number of different applications that traditional eco-solvent printers or water-based printers can produce.
- HP image permanence and scratch, smudge, and water resistance estimates by HP Image Permanence Lab. Outdoor display permanence tested according to SAE J2527 using HP Latex, low-solvent, and eco-solvent inks on a range of media, including HP media; in a vertical display orientation in simulated nominal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change. Scratch, smudge, and water resistance tested using HP Latex, low-solvent, and eco-solvent inks on a wide range of media, including HP media; water resistance is comparable when printed on water-resistant substrates. Laminated display permanence for latex/low-solvent comparison using Neschen Solvoprint Performance Clear 80 laminate; for latex/eco-solvent comparison using G8C clear glass 1.7 mil hot laminate. Results may vary based on specific media performance and scratch testing methodology. For more information, see www.hp.com/go/supplies/print/permanence.
- For best results, print on polyester fabric that does not stretch. Performance may vary depending on media. Please consult your media supplier for compatibility details.
- The HP printer is subject to the HP hardware warranty.
- Some warranty limitations apply, see the HP Performance Warranty for HP Air Release Adhesive Gloss Cast Vinyl at www.hp.com/go/HPMediaWarranties.
- Printers using HP Latex Inks use internal heaters to dry and cure the latex polymer film. Some substrates may have inherent odor.
- HP PVC-free Wall Paper printed using HP Latex Inks is listed in the GREENGUARD product listing for low emitting products and is tested to the GREENGUARD Children & Schools standard. The print is neither GREENGUARD nor GREENGUARD Children & Schools Certified. The GREENGUARD Environmental Institute is an American National Standards Institute (ANSI) authorized standards developer that establishes acceptable indoor air standards for indoor products, environments, and buildings. See www.greenguard.org.
- The Committee for Health-related Evaluation of Building Products, AgBB, establishes the fundamentals for a uniform and reproducible health-related evaluation of building products in Germany, including criteria for testing and an evaluation scheme for health-related evaluation of VOC emissions from building products used for application indoors.
- Special ventilation is not required to meet US OSHA requirements on occupational exposure to VOCs from HP Latex Inks. Special ventilation equipment installation is at the discretion of the customer—no specific HP recommendation is intended. Customers should consult state and local requirements and regulations.
- HP offers the HP Large-format Media take-back program in the U.S., Europe, and Canada (as of June 1, 2010), through which most HP recyclable signage media can be returned, availability varies. Some recyclable papers can be recycled through commonly available recycling programs. For details visit www.hp.com/recycle. Aside from this program, recycling opportunities for these products are currently only available in limited areas. Customers should consult local recycling resources for recycling these products.
- In the circa 50 countries and territories in which the HP Planet Partners program operates. Program features and availability varies. Where this program is not available, and for other consumables not included in the program, consult the Material Safety Data Sheet (MSDS) available at www.hp.com/go/ecodata to determine appropriate disposal.
- Speed based on printing using full width (152.4 cm/60 in). Measured on an HP Designjet L25500 60-in Printer.
- Recommended up to 30 m (100 ft).

FOR MORE INFORMATION, VISIT OUR WEBSITE AT
WWW.HP.COM/GO/DESIGNJETL25500

© Copyright 2010, 2009 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. 4AA2-7663ENW, May 2010

